



Construction:

	RG 11/ U-4 F AL	RG 11/ U-6 F CCA
Inner Conductor (mm) Ø	1,63 Cu	1,63 Cu
Insulation (mm) Ø	FPE 7,10	FPE 7,10
Outer Conductor	AL-PES	Cu-PES
Braid	%55 AL.	%55 CCA
Outer sheath	PVC	PVC
Colour	Black-Orange	Black-Green
Outer Diameter (mm)	10,10	10,10

- Cu : Plain Copper
- Cu-PES : Plain Copper Coated Polyester Tape
- Al : Aluminium
- FPE : Physical Foam Polyethylene
- CCA : Copper Clad Aluminium Conductor
- PE : Polyethylene
- AL-PES : Aluminium Polyester Tape
- HFFR : Halogen Free, Flame Retardant

Technical data and tests:

	RG 11/ U-4 F AL	RG 11/ U-6 F CCA
Propagation velocity ratio	0,82	0,82
Insulation resistance	> 2000	> 2000
Capacitance (pF/m)	54	54
Attenuation (20° C)	(dB/100m)	(dB/100m)
100 MHz	4,6	4,4
200 MHz	6,7	6,4
400 MHz	8,7	8,5
600 MHz	11,2	11,0
800 MHz	13,3	12,8
1000 MHz	14,6	14,3
1350 MHz	17,8	17,2
1750 MHz	20,5	19,8
2150 MHz	23,1	22,0
Flame Test	IEC 60332-1 EN 50265-2-1	IEC 60332-1 EN 50265-2-1
Operating Voltage	2,0 kV	2,0 kV
Test Voltage	5,0 kV	5,0 kV
Min. Bending Radius (mm)	15xD	15xD
Temperature Range	-40 +70°C	-40 +70°C

Applications:

These 75 ohm cables are used as connection cables in CATV, CCTV, satellite and common antenna TV systems for which low attenuation is necessary.

