



RG 59/ U-4 F



RG 59/ U-6 F



Construction:

	RG 59/ U-4 F Al	RG 59/ U-6 F CCA
Inner Conductor (mm) Ø	0,80 Cu	0,80 Cu
Insulation (mm) Ø	FPE 3,66	FPE 3,66
Outer Conductor	AL-PES	Cu-PES
Braid	%55 Al.	%55 CCA
Outer sheath	PVC	PVC
Colour	White	White
Outer Diameter (mm)	5,80	5,80

Cu : Plain Copper
 Cu-PES : Plain Copper Coated Polyester Tape
 Al : Aluminium
 FPE : Physical Foam Polyethylene
 CCA : Copper Clad Aluminium Conductor
 PE : Polyethylene
 AL-PES : Aluminium Polyester Tape
 HFFR : Halogen Free, Flame Retardant

Technical data and tests:

	RG 59/ U-4 F Al	RG 59/ U-6 F CCA
Propagation velocity ratio	0,82	0,82
Insulation resistance	> 2000	> 2000
Capacitance (pF/m)	54	54
Attenuation (20° C)	(dB/100m)	(dB/100m)
100 MHz	8	7,9
200 MHz	11,5	11,3
400 MHz	17,1	16,8
600 MHz	21,2	20,8
800 MHz	23,6	23,2
1000 MHz	26,6	26,1
1350 MHz	31,3	30,8
1750 MHz	35,8	35,3
2150 MHz	40,3	39,2
Flame Test	IEC 60332-1 EN 50265-2-1	IEC 60332-1 EN 50265-2-1
Operating Voltage	1,1 kV	1,1 kV
Test Voltage	2,5 kV	2,5 kV
Min. Bending Radius (mm)	10xD	10xD
Temperature Range	-40 +70°C	-40 +70°C

Applications:

These 75 ohm cables are used as connection cables in CATV, CCTV, satellite and common antenna TV systems for which low attenuation is necessary.

