



# HALLEY CABLES

# BIRTFLEX 659 PUR

## Control cables

PP (polypropylene) insulated, PUR sheathed, extra flexible, oil resistant cable



### Construction:

- Conductor : extra flexible copper wires, plain; IEC 60228 Class 6, DIN EN 60228 Class 6.
- Insulation : PP (polypropylene) compound, 9Y.
- Core identif. : numbered cores or colour coded cores.
- Lay-up : cores laid up in layers of optimum pitch.
- Separator : textile material, at each lay-up layer.
- Outer sheath : PUR (polyurethane) compound, 11YM1.
- Sheath colour : RAL 7001, Grey (to be agreed upon the shade of grey).

### Technical data and tests:

- Standard : HD 21.13 S1;  
DIN VDE 0281-13;  
DIN VDE 0282-10.
- Insulation resistance : min. 50 M $\Omega$ /km.
- Rated voltage U<sub>0</sub>/U : 300 / 500 V.
- Test voltage (50 Hz) : 2000 V.
- Temperature range : fixed : - 30° C ~ + 80° C;  
mobile: - 5° C ~ + 70° C.
- Min. bending radius : fixed : 4 x D;  
mobile: 7.5 x D.
- Flame retardance test : IEC 60332-1 & EN 50265-2-1.
- Oil test : IEC 60811-2-1.

### Applications:

This control cable is resistant to oil, cold and extreme mechanical load and designed for applications where high cable flexibility is required. This type is more economical than 6512 PUR; it has a high service period, can be used for instrumentation, control and connection of control units in mechanical tool construction, conveyor and assembly lines, production lines. It can be used in any areas where continuous bending loads require free movement without pulling force and areas where low tensile load forced movement is required. It can be installed in dry, humid, wet and cold places.

www.halleycables.com

**BIRTFLEX 659 PUR**



**HALLEY CABLES**

# BIRTFLEX 659 PUR

**Control cables**

PP (polypropylene) insulated, PUR sheathed, extra flexible, oil resistant cable

[www.halleycables.com](http://www.halleycables.com)

## DIMENSIONS

No. of Cores x Cross Section mm <sup>2</sup>	Approx. Outer Diameter mm	Copper Weight Kg/km	Approx. Cable Weight Kg/km
3G0.50	6,6	14	55
4G0.50	7,2	19	65
5G0.50	7,8	24	80
7G0.50	9,4	34	115
12G0.50	11,7	58	175
18G0.50	14,5	87	250
25G0.50	15,9	120	345
34G0.50	19,3	163	475
3G0.75	6,9	22	60
4G0.75	7,7	29	75
5G0.75	8,7	36	100
7G0.75	9,9	50	140
12G0.75	12,4	86	215
18G0.75	14,5	130	305
25G0.75	17,9	180	425
34G0.75	20,5	245	590
3G1.0	7,4	29	70
4G1.0	8,0	38	95
5G1.0	9,3	48	120
7G1.0	10,1	67	150
12G1.0	13,5	116	250
18G1.0	15,7	173	385
25G1.0	19,5	240	535
34G1,0	21,9	326	700
3G1.5	8,1	43	90
4G1.5	9,2	58	125
5G1.5	10,2	72	155
7G1.5	11,3	101	200
12G1.5	14,4	174	325
18G1.5	17,3	260	505
25G1.5	21,0	360	690
34G1.5	23,4	489	920

**BIRTFLEX 659 PUR**