





**HALLEY CABLES**

**MYYM - H05VVH2-F**

**H05VV-F**

**PVC insulated and sheathed cords**

www.halleycables.com

**DIMENSIONS**

Cord size	Max. copper wire diameter mm	Radial insulation thickness mm	Radial thickness of sheath mm	Max. resistance at 20°C Ω/km	Insulation resistance at 70°C, min MΩ*km	Nominal outer diameter mm	Mass kg/km
<b>H05VVH2-F</b>							
2x0.75	0.21	0.6	0.8	26	0.011	4x6.4	59
2x1	0.21	0.6	0.8	19.5	0.01	4.1x6.6	67
<b>H05VV-F</b>							
2x0.75	0.21	0.6	0.8	26	0.011	6.2	55
2x1	0.21	0.6	0.8	19.5	0.01	6.6	65
2x1.5	0.26	0.7	0.8	13.3	0.01	7.4	84
2x2.5	0.26	0.8	1	7.98	0.0095	9.2	132
2x4	0.31	0.8	1.1	4.95	0.0078	10.8	199
3x0.75	0.21	0.6	0.8	26	0.011	6.4	64
3x1	0.21	0.6	0.8	19.5	0.01	6.9	76
3x1.5	0.26	0.7	0.9	13.3	0.01	7.9	102
3x2.5	0.26	0.8	1.1	7.98	0.0095	9.8	161
3x4	0.31	0.8	1.2	4.95	0.0078	11.4	238
4x0.75	0.21	0.6	0.8	26	0.011	7.2	81
4x1	0.21	0.6	0.9	19.5	0.01	7.9	100
4x1.5	0.26	0.7	1	13.3	0.01	9	134
4x2.5	0.26	0.8	1.1	7.98	0.0095	10.9	205
4x4	0.31	0.8	1.2	4.95	0.0078	12.7	303
5x0.75	0.21	0.6	0.9	26	0.011	8	101
5x1	0.21	0.6	0.9	19.5	0.01	8.6	120
5x1.5	0.26	0.7	1.1	13.3	0.01	10	167
5x2.5	0.26	0.8	1.2	7.98	0.0095	12.1	254
5x4	0.31	0.8	1.4	4.95	0.0078	14.3	380

**MYYM - H05VVH2-F - H05VV-F**

