



HALLEY CABLES

RE-2Y(St)Y-fl MP 70° C

CU/PE/OSCR/PVC

Instrumentation Cables PVC DK PE 500 V

PE insulated, collective screened, PVC sheathed cable

DIMENSIONS

No. of cores x cross section mm ²	Approx. outer diameter mm	Copper weight kg/km	Approx. cable weight kg/km
1x2x0,50	6,2	14	40
1x2x0,75	6,6	19	50
1x2x1	7,0	24	55
1x2x1,3	7,5	30	65
1x2x1,5	7,8	34	70
2x2x0,50	9,2	24	70
2x2x0,75	9,8	34	85
2x2x1	10,5	43	100
2x2x1,3	11,5	55	120
2x2x1,5	12,1	62	135
4x2x0,50	10,9	43	110
4x2x0,75	11,7	62	135
4x2x1	12,5	82	165
4x2x1,3	13,7	105	200
4x2x1,5	14,4	120	225
5x2x0,50	11,4	53	130
5x2x0,75	12,2	77	160
5x2x1	13,1	101	190
5x2x1,3	14,4	130	240
5x2x1,5	15,1	149	265
6x2x0,50	12,2	62	145
6x2x0,75	13,2	91	185
6x2x1	14,3	120	230
6x2x1,3	15,5	155	280
6x2x1,5	16,4	178	315
8x2x0,50	13,9	82	190
8x2x0,75	15,0	120	240
8x2x1	16,3	158	300
8x2x1,3	17,7	204	360
8x2x1,5	18,5	235	400
10x2x0,50	15,2	101	225
10x2x0,75	16,6	149	295
10x2x1	17,9	197	360
10x2x1,3	19,6	254	445
10x2x1,5	20,6	293	495
12x2x0,50	16,6	120	270
12x2x0,75	17,9	178	345
12x2x1	19,5	235	425

www.halleycables.com

RE-2Y(St)Y-fl MP 70° C ~ CU/PE/OSCR/PVC





HALLEY CABLES

RE-2Y(St)Y-fl MP 70° C

CU/PE/OSCR/PVC

Instrumentation Cables PVC DK PE 500 V

PE insulated, collective screened, PVC sheathed cable

www.halleycables.com

DIMENSIONS

No. of cores x cross section mm ²	Approx. outer diameter mm	Copper weight kg/km	Approx. cable weight kg/km
12x2x1,3	21,2	304	520
12x2x1,5	22,4	350	590
16x2x0,50	18,7	158	340
16x2x0,75	20,4	235	445
16x2x1	22,2	312	555
16x2x1,3	24,4	404	690
16x2x1,5	25,6	466	770
20x2x0,50	20,7	197	420
20x2x0,75	22,7	293	550
20x2x1	24,6	389	680
20x2x1,3	27,0	504	850
20x2x1,5	28,3	581	950
24x2x0,50	22,6	235	500
24x2x0,75	24,7	350	650
24x2x1	26,6	466	800
24x2x1,3	29,2	604	995
24x2x1,5	30,9	696	1130

RE-2Y(St)Y-fl MP 70° C ~ CU/PE/OSCR/PVC

